Technical data sheet

Rev.0 Mar 2024

R100-Low Carbon 550-L

Identification [1]

CAS number: 67774-74-7 EC number: 267-051-0

Description

NextLab-R100-Low Carbon 550-L is a linear alkylbenzene (LAB) which, in addition to incorporating 100% certified renewable raw materials in the production process, has been produced using energy from renewable sources. This product maintains the same technical specifications as its fossil counterpart PetreLAB 550. It is a blend of C10-C13 homologues with a low content of 2-phenyl isomers (15-21%). Detal Flex 2 Phenyl technology is used for its production.
In addition, our production plants have a certification system that allows us to identify and guarantee sustainable production from the origin of the product to its delivery, using the mass balance methodology applied to matter and energy.
It is offered in two versions depending on its renewable raw material content: 68% (NextLab-R-Low Carbon 550-L) and 100% (NextLab-R100-Low Carbon 550-L).

Aplication

NextLab-R100-Low Carbon 550-L is mainly used as a raw material to produce Linear Alkylbenzene Sulfonic Acid (LABSA) through sulfonation reaction, which is then neutralized to produce sodium linear alkylbenzene sulfonate (LAS), the main anionic surfactant used for the formulation of biodegradable detergents. It is also used in dishwashers and other household cleaners, as well as in a wide range of applications in other industries.

Typical properties

Property		Unit	Method	Typical Value
Density	@ 15ºC	g/ml	ASTM D 4052	0.86
Saybolt Colour			ASTM D 156	30
Bromine Index		mg/100g	ASTM D 2710	1-2
Carbon chain distribution		%wt	UOP 673	
<5 phenyl C10				0.9-1.1
phenyl C10				11-13
phenyl C11				31-35
phenyl C12				33-40
phenyl C13				16-18
phenyl C14				0.3-0.4
>phenyl C14				<0.1
2 phenyl alkanes		%wt	UOP 673	20-21
Total linear alkylbenzene			UOP 673	>90
Total branched alkylbenzene			UOP 673	<10
Molecular weight		g/mol	UOP 673	240
Paraffins		%wt	UOP 673	≤0.1
Tetralins and Indans		%wt	EN 13405	<0.5
Water		ppm	UOP 481	<50
Viscosity	@ 40ºC	cSt	ASTM D 445	4.23
Flash point		ºC	ASTM D 93	140
Sulfonability		%wt	LSC_CQPM 704	98.5
Refractive index	@ 20ºC		ASTM D 1218	1.483

The Sodium Sulfonate obtained in the neutralization of the Sulphonic Acid derived from NextLab-R100-Low Carbon 550-L complies with biodegradability requirements laid down in C.E detergent regulation CE nº 648/2004.

*All the data provided does not imply the replacement of the Moeve Specification Sheets or Safety Sheets

[1] For the latest updates on these numbers, please consult the safety data sheet available at: chemicals.moeveglobal.com

Standard packaging

Available in trucks, flexitanks 20ft, isotanks, railcars and bulk vessels.

Storage and handling

Store in accordance with local regulations.
Carbon steel is preferred for pipes and storage in contact with NextLab-R100-Low Carbon 550-L.
For more information, refer to the Safety Data Sheet.

Health and safety

Refer to the Material Safety Data Sheet (MSDS).

Contact us for more info at: techsupport@moevechemicals.com
Moeve Chemicals, S.A.U. Plaza Pablo Ruiz Picasso, 1. Edificio Torre Picasso. 28020 Madrid