

# PETROSOL D 80

## IDENTIFICATION

CAS number: 64742-47-8

EC number: 926-141-6 (prov.)

## DESCRIPTION

PETROSOL D 80 is a hydrogenated naphtha-kerosene cut with a typical flash greater than or equal to 72°C. It has a very low aromatic and sulfur content, with a low penetration smell.

## APPLICATIONS

Given its low aromatic content and its imperceptible smell, it is used in paints and varnishes, as fuel, as a solvent, in lubricants and multipurpose oils, in drilling fluids, in insecticides and home air fresheners, as a degreaser, etc.

## TYPICAL PROPERTIES

Property		Unit	Value
Density	@ 15°C	kg/l	0,81
Color Saybolt			+30
Bromine Index		mg Br/100g	<10
Distillation range			
Initial		°C	195
Final		°C	258
Vapor pressure (calc.)	@ 20°C	kPa	0,02
Aromatics		% (wt)	0,1
Benzene		ppm	<1
Flash point (close cup)		°C	75
Aniline point		°C	70
Kauri-Butanol index			30,5
Melting point		°C	-56,0
Kinematic viscosity	@ 25°C	cSt	2,05
	@ 40°C	cSt	1,60

## STANDARD PACKAGING


Available in trucks and vessels

## STORAGE AND HANDLING

Store in accordance with local regulations.

## HEALTH AND SAFETY

PETROSOL D 80 MSDS is available. For more info, contact Cepsa product stewardship.



For more info, please contact us:

[techsupport@cepsa.com](mailto:techsupport@cepsa.com)

Cepsa Quimica S.A.  
Torre Cepsa. Paseo de la Castellana 259 A  
28046 Madrid (Spain)

