

Identification ¹

Número CAS: 85536-14-7

Número EC: 287-494-3

Description

NextLabsa-R 550-L is a linear alkylbenzene sulphonic acid (LABSA) that incorporates certified renewable raw materials in its production process and maintains the same technical specifications as its fossil counterpart, which varies depending on the production technology: Petresul 550, in the case of Detal Flex 2-Phenyl technology or DetenLAS 320 in the case of HF technology; but which in any case is a mixture of C10-C13 homologues with low content of 2-phenyl isomers: 15-21% for the one based on Petresul 550 and 21% max for the one based on DetenLAS 320.

In addition, our production plants have a certification system that makes it possible to identify and guarantee sustainable production from the origin of the product to its delivery, using the mass balance methodology.

It is offered in two versions depending on its renewable raw material content: 68% (NextLabsa-R68 550-L) and 100% (NextLabsa-R100 550-L).

Application

NextLabsa-R 550-L is exclusively used for the production of sodium linear alkylbenzene sulphonate (LAS) in the neutralisation process. LAS is the most important anionic surfactant used for the formulation of biodegradable detergents. It is also used in dishwashers and other household cleaners, as well as in a wide range of applications in other industries.

Typical properties

Property	Unit	Method	Value
Appearance	-	Visual	Brown Viscous Liq.
Odour	-	Organoleptic	Spicy
Klett color (5% A.M.)	%wt	CQ PM LC 802.4	18
Active matter (alkylbenzene sulfonic acid)	%wt	CQ PM LC 802.7	97.2
Un sulfonated organic matter (Free oil)	%wt	CQ PM LC 802.5	1.5
Free sulphuric acid	%wt	CQ PM LC 802.2	0.8
Average molecular weight	g/mol	UOP 673	320
Water	%wt	CQ PM LC 305	0.5
Viscosity @ 40°C	cSt	CQ PM LC 363	400
Density @ 25°C	g/ml	CQ PM LC 807	1.05
Pour point	°C	ASTM D 5950	6.5
Total acidity	mg KOH/g	CQ PM LC 802.1	179

The sodium sulfonate obtained in the neutralization of NextLabsa-R 550-L complies with biodegradability requirements laid down in the C.E detergent regulation CE n° 648/2004.

*All the data provided does not imply the replacement of the Moeve Specification Sheets or Safety Sheets

¹ For the latest updates on these numbers, please consult the safety data sheet available at: chemicals.moeveglobal.com

Standard packaging

Available in trucks and isotanks.

Storage and handling

Store in accordance with local regulations.

Keep away from direct sunlight.

Recommended storage temp: 30-40°C. At lower temperatures, its viscosity can lead to pumping problems.

Tanks and pipes material: Stainless steel 316.

SO3 gases can accumulate in storage tanks.

Storage should not exceed six months from the manufacturing date.

For more information, refer to the Safety Data Sheet.

Health and safety

Refer to the Material Safety Data Sheet (MSDS)..