

Petrosol 15A 15/20

Identification ¹

CAS Number: 64742-82-1
(Only valid outside Europe)

EC Number: 919-446-0

Description

Petrosol 15A 15/20 is a kerosene fraction, with a typical initial and final distillation range of 150-200°C. It has a limited aromatics content.

Application

It is used in solvents, adhesives, paints, varnishes, inks, etc.

Typical properties

Property		Unit	Method	Value
Density	@ 15°C	kg/l	ASTM D 4052	0.800
Color Saybolt		-	ASTM D 6045	+30
Bromine Index		mg Br/100g	ASTM D 2710	164
Distillation Range			ASTM D 86	
Initial		°C		168.6
Dry point		°C		211.2
Aromatics		% v/v	ASTM D 6379	16
Sulphur		ppm wt	ASTM D 5453	<1
Cumene		%wt	ASTM D 93	53
Flash Point		°C	ASTM D 6229	<0.10
Aniline Point		°C	ASTM D 611	55.4
Kauri-Butanol value			ASTM D 1133	38
Viscosity (Kinem.)	@ 25°C	cSt	ASTM D 445	1.71
Viscosity (Kinem.)	@40°C	cSt	ASTM D 445	1.20

*All the data provided does not imply the replacement of the Moeve Specification Sheets or Safety Sheets

¹ For the latest updates on these numbers, please consult the safety data sheet available at: chemicals.moeveglobal.com

Transport

Available in trucks and vessels.

Storage and handling

Store in accordance with local regulations.

Health and safety

Refer to the Material Safety Data Sheet (MSDS).

Contact us for more info at: techsupport@moevechemicals.com

Moeve Chemicals, S.A.U. Plaza Pablo Ruiz Picasso, 1. Edificio Torre Picasso. 28020 Madrid