

Petrosol 20A 19/22

Identification ¹

CAS Number: 64742-82-1
(Only valid outside Europe)

EC Number: 919-164-8

Description

Petrosol 20A 19/22 is a kerosene fraction, with a typical initial and final distillation range of 190-220°C. It has a limited aromatics content.

Application

It is used in solvents, adhesives, paints, varnishes, inks, etc.

Typical properties

Property		Unit	Method	Value
Density	@ 15°C	kg/l	ASTM D 4052	0.814
Color Saybolt		-	ASTM D 6045	+29
Bromine Index		mg Br/100g	ASTM D 2710	151
Distillation Range			ASTM D 86	
Initial		°C		177
Dry point		°C		220
Aromatics		% wt	ASTM D 7504	21
Cumene		% wt	ASTM D 7504	<0.10
Sulphur		ppm wt	ASTM D 5453	<1
Flash Point		°C	ASTM D 93	63
Aniline Point		°C	ASTM D 611	57
Kauri-Butanol value		-	ASTM D 1133	37.5
Viscosity (Kinem.)	@ 25°C	cSt	ASTM D 445	1.63
Viscosity (Kinem.)	@40°C	cSt	ASTM D 445	1.18

*All the data provided does not imply the replacement of the Moeve Specification Sheets or Safety Sheets

¹ For the latest updates on these numbers, please consult the safety data sheet available at: chemicals.moeveglobal.com

Transport

Availale in trucks and vessels.

Storage and handling

Store in accordance with local regulations.

Health and safety

Refer to the Material Safety Data Sheet (MSDS).

Contact us for more info at: techsupport@moevechemicals.com

Moeve Chemicals, S.A.U. Plaza Pablo Ruiz Picasso, 1. Edificio Torre Picasso. 28020 Madrid