

Petrosol 95A 16/18

Identification ¹

CAS Number: 64742-95-6
(Only valid outside Europe)

EC Number: 918-668-5

Description

Petrosol 95A 16/18 is a mix of aromatic hydrocarbons, mainly C9-C10, with a typical initial and final distillation range of 160-180°C

Application

Thanks to its strong solvent power, it is widely used in adhesives and paints.

Typical properties

Property		Unit	Method	Value
Density	@ 15°C	kg/l	ASTM D 4052	0.877
Color Saybolt		-	ASTM D 6045	+30
Bromine Index		mg Br/100g	ASTM D 2710	151
Distillation Range			ASTM D 86	
Initial		°C		162
Dry Point		°C		171
Aromatics		% wt	ASTM D 7504	99.9
Benzene		ppm wt	ASTM D 7504	<10
Flash Point		°C	ASTM D 93	50
Cumene		% wt	ASTM D 6229	<0.10
Aniline Point		°C	ASTM D 611	11
Kauri-Butanol value		-	ASTM D 1133	90
Viscosity (Kinem.)	@ 25°C	cSt	ASTM D 445	0.88
Viscosity (Kinem.)	@ 40°C	cSt	ASTM D 445	0.71
Pour Point		°C	ASTM D 5902	-105

*All the data provided does not imply the replacement of the Moeve Specification Sheets or Safety Sheets

¹ For the latest updates on these numbers, please consult the safety data sheet available at: chemicals.moeveglobal.com

Transport

Available in trucks and vessels.

Storage and handling

Store in accordance with local regulations.

Health and safety

Refer to the Material Safety Data Sheet (MSDS).

Contact us for more info at: techsupport@moevechemicals.com

Moeve Chemicals, S.A.U. Plaza Pablo Ruiz Picasso, 1. Edificio Torre Picasso. 28020 Madrid