

# Petrosol D 60/95

## Identification <sup>1</sup>

CAS Number: 64742-49-0  
(Only valid outside Europe)

EC Number: -

## Description

Petrosol D 60/95 is a mix of C6-C7 isomers with a boiling range of 60-95°C, which allows a gradual evaporation of the solvent. It contains a very low content in aromatics and other impurities, with low-penetration smell.

## Application

Petrosol D 60/95 is mainly used in adhesives and cleaning. Also in paints/coatings.

## Typical properties

Property		Unit	Method	Value
Density	@ 15°C	kg/l	ASTM D 4052	0.677
Color Saybolt		-	ASTM D 6045	+30
Bromine Index		mg Br/100g	ASTM D 2710	<10
Distillation Range			ASTM D 1078	
Initial		°C		65
Dry point		°C		90
Aromatics		% v/v	ASTM D 5134	< 0.005
Benzene		% v/v	ASTM D 6229	< 0.001
Sulphur		ppm wt	ASTM D 4045	<1
Flash Point		°C	ASTM D 56	<0
Aniline Point		°C	ASTM D 611	-
Kauri-Butanol value			ASTM D 1133	28
Viscosity (Kinem.)	@ 25°C	cSt	ASTM D 445	0.48
Viscosity (Kinem.)	@40°C	cSt	ASTM D 445	0.40

\*All the data provided does not imply the replacement of the Moeve Specification Sheets or Safety Sheets

<sup>1</sup> For the latest updates on these numbers, please consult the safety data sheet available at: [chemicals.moeveglobal.com](https://chemicals.moeveglobal.com)

## Transport

Available in trucks and vessels.

## Storage and handling

Store in accordance with local regulations.

## Health and safety

Refer to the Material Safety Data Sheet (MSDS).

Contact us for more info at: [techsupport@moevechemicals.com](mailto:techsupport@moevechemicals.com)

Moeve Chemicals, S.A.U. Plaza Pablo Ruiz Picasso, 1. Edificio Torre Picasso. 28020 Madrid