

Petrosol D 40

Identification ¹

CAS Number: 64742-48-9
(Only valid outside Europe)

EC Number: 919-857-5

Description

Petrosol D 40 is a hydrogenated naphtha-kerosene cut with a typical distillation range of 150-200°C. It has a very low aromatic content, with a low penetration smell.

Application

Due to its low aromatic content and nearly imperceptible odor, it is used in paints and varnishes, as a fuel, as a solvent, in lubricants and multipurpose oils, in drilling fluids, in insecticides and household air fresheners, and as a degreasing agent

Typical properties

Property		Unit	Method	Value
Density	@ 15°C	kg/l	ASTM D 4052	0.781
Color Saybolt		-	ASTM D 6045	+29
Bromine Index		mg Br/100g	ASTM D 2710	1.5
Distillation Range			ASTM D 86	
Initial		°C		163
Dry point		°C		204
Aromatics		% v/v	UOP 495	< 0.1
Sulphur		ppm wt	ASTM D 5453	<1
Flash Point		°C	ASTM D 93	49
Aniline Point		°C	ASTM D 611	67.8
Kauri-Butanol value			ASTM D 1133	32
Viscosity (Kinem.)	@ 25°C	cSt	ASTM D 445	1.40
Viscosity (Kinem.)	@40°C	cSt	ASTM D 445	1.15
Pour Point		°C	ASTM D 5950	<-60

*All the data provided does not imply the replacement of the Moeve Specification Sheets or Safety Sheets

¹ For the latest updates on these numbers, please consult the safety data sheet available at: chemicals.moeveglobal.com

Transport

Available in trucks and vessels.

Storage and handling

Store in accordance with local regulations.

Health and safety

Refer to the Material Safety Data Sheet (MSDS).

Contact us for more info at: techsupport@moevechemicals.com

Moeve Chemicals, S.A.U. Plaza Pablo Ruiz Picasso, 1. Edificio Torre Picasso. 28020 Madrid